



SIPABOARDS DRIVE

TECH SPECS - B2B



MODEL	NEO	TOURER	ALL-ROUNDER	FISHERMAN
-------	-----	--------	-------------	-----------

DIMENSIONS

Board	336 x 77 x 15 cm 11' x 30" x 6"	365 x 82 x 15 cm 12' x 32,2" x 6"	336 x 90 x 15 cm 11' x 35,4" x 6"	336 x 90 x 15 cm 11' x 35,4" x 6"
Drive	52 x 21 x 15 cm 20.5 x 8.3 x 5.9"	52 x 21 x 15 cm 20.5 x 8.3 x 5.9"	52 x 21 x 15 cm 20.5 x 8.3 x 5.9"	52 x 21 x 15 cm 20.5 x 8.3 x 5.9"
Remote	78 x 41 x 42 mm 3.1 x 1.6 x 1.7"	78 x 41 x 42 mm 3.1 x 1.6 x 1.7"	78 x 41 x 42 mm 3.1 x 1.6 x 1.7"	78 x 41 x 42 mm 3.1 x 1.6 x 1.7"
Battery	18 x 8,5 x 5,5 cm 7.1 x 3.4 x 2.2"	18 x 8,5 x 5,5 cm 7.1 x 3.4 x 2.2"	18 x 8,5 x 5,5 cm 7.1 x 3.4 x 2.2"	18 x 8,5 x 5,5 cm 7.1 x 3.4 x 2.2"
Drive Package <small>(including drive, remote, battery, charging cable, inflation hose, leash, repair kit)</small>	55 x 24 x 21 cm 21.6 x 9.4 x 8.3"	55 x 24 x 21 cm 21.6 x 9.4 x 8.3"	55 x 24 x 21 cm 21.6 x 9.4 x 8.3"	55 x 24 x 21 cm 21.6 x 9.4 x 8.3"
Board Package <small>(including board, board bag, paddle, fin)</small>	94 x 51 x 27 cm 37 x 20 x 10,6"	94 x 51 x 22 cm 37 x 20 x 8,6"	99 x 51 x 22 cm 38 x 20 x 8,6"	99 x 54 x 24 cm 37 x 21 x 9,5"

WEIGHT

Board	7,7 kg / 17 lbs	8,7 kg / 19 lbs	10 kg / 22 lbs	14 kg / 30,9 lbs
Drive	3,1 kg / 6,8 lbs	3,1 kg / 6,8 lbs	3,1 kg / 6,8 lbs	3,1 kg / 6,8 lbs
Remote	0,1 kg / 0.2 lbs	0,1 kg / 0.2 lbs	0,1 kg / 0.2 lbs	0,1 kg / 0.2 lbs
Battery	1,15 kg / 2.5 lbs	1,15 kg / 2.5 lbs	1,15 kg / 2.5 lbs	1,15 kg / 2.5 lbs
Drive Package <small>(including drive, remote, battery, charging cable, inflation hose, leash, repair kit)</small>	5 kg / 11 lbs	5 kg / 11 lbs	5 kg / 11 lbs	5 kg / 11 lbs
Board Package <small>(including board, board bag, paddle, fin)</small>	14,5 kg / 32 lb	15 kg / 33 lb	17 kg / 38 lb	18 kg / 39 lbs

VOLUME

Volume	260 l	320 l	340 l	350 l
--------	-------	-------	-------	-------

BATTERY

Type	Li-Ion voltage: 14.4V capacity: 11Ah power: 158Wh certificates: UN38.3, CE, FCC, ROHs, MSDS			
Drive recharging time	3h	3h	3h	3h
Drive operating time	1 st speed: 3 h 2 nd speed: 2 h 3 rd speed: 1 h	1 st speed: 3 h 2 nd speed: 2 h 3 rd speed: 1 h	1 st speed: 3 h 2 nd speed: 2 h 3 rd speed: 1 h	1 st speed: 3 h 2 nd speed: 2 h 3 rd speed: 1 h
Remote control recharging time	2h	2h	2h	2h
Remote control operating time	8h	8h	8h	8h

TEMPERATURE

Pumping	5 - 35 °C 41 - 95 F	5 - 35 °C 41 - 95 F	5 - 35 °C 41 - 95 F	5 - 35 °C 41 - 95 F
Driving	5 - 40 °C 41 - 104 F	5 - 40 °C 41 - 104 F	5 - 40 °C 41 - 104 F	5 - 40 °C 41 - 104 F